



from 75 to 120 HP



Ø 8 in max

## FORESTRY MULCHER WITH FIXED TOOTH ROTOR FOR SKID STEERS.

Robust and compact, the UML/SSL is renowned for its ergonomic design that guarantees excellent visibility for the operator during various situations. Thanks to the diverter valve kit option, it can be utilized with any brand of skid steer on the market. The VT version with automatic variable displacement hydraulic motor increases productivity by up to 50% and simultaneously reduces fuel consumption.

STANDARD EQUIPMENT	
Anti dust machine body	Double line protection chains
Belt transmission	Anti-dust rear hood
110/60cc variable torque hydraulic piston motor - (34 - 53 GPM)	Motor integrated into the frame
Hydraulic hoses	OPTIONS
Hydraulic rear hood	Customized setting hydraulic motor
Adjustable skids	Diverter valve
Welded counter blade	Oil cooler kit (roof mount or internal)
Working pressure control gauge	Hydraulic couplers
Pushing frame	Electrical connector
	Multiple tooth options

## FEATURES

- Low profile frame design**  
for excellent working visibility
- Enclosed door drive**  
revolutionary system of door opening/closing that prevents dirt from entering into the service areas of the machine
- Reinforced sides**  
increases axial load bearing
- Heavy duty adjustable skids**
- Aggressive body design**  
the protruding rotor allows more material to process without dragging material
- External pressure control Gauge**
- Poly-Chain® Carbon transmission belts**  
for solid power conversion and maximum productivity
- Double row protection chains**  
knocks down the material exiting out the back, increasing safety

THE STARTING POINT  
FOR ANYONE WITH A SKID STEER



## MAIN OPTIONS

- VT motor**  
adjusts the motor to obtain the maximum performance from any skid steer
- Diverter valve to control hood cylinders**  
to control the opening and closing of the hydraulic door
- Oil cooler kit**  
for working in hot climates
- Roof mounted cooler**  
for working in hot climates

MODEL	Engine (HP)		Flow rate (gal/min)		Pressure (PSI)		Working width (in)	Total width (in)	Weight (lbs)	Max shredding diameter (in)	No. teeth type	
	min	max	min	max	min	max					C/3+C/3/SS	I-C/3/SS
UML/SSL/VT 125*	75	120	34	53	2900	5000	53	65	2425	8	26+2	36+2
UML/SSL/VT 150*	75	120	34	53	2900	5000	62	74	2756	8	32+2	42+2
UML/SSL/VT 175*	75	120	34	53	2900	5000	72	83	2954	8	36+2	50+2

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.  
\*Variable displacement hydraulic motor.